

TEMPSEN SOLUTION PARTNER IN SCANNER TECHNOLOGY

Mp Based Process Scanner

TTS Series

Tempsen Process Scanner accept input RTD, Thermocouple Voltage, Current. The scanner suitable for Temperature, Pressure, Humidity, Level, Flow, RPM, Voltage, Current. The input is passed through suitable filters to eliminate unwanted signals. The Scanner have hold, Program, scan LED indication and scanning time adjustable. This is a high performance series equipped to handle virtually any process documentations in mechanical and system engineering. Cold junction compensation is standard feature in Thermocouple input.



Tempsen Scanner provide skip facility for all channels and offset for all channels. Large local display size (1", 2", 6"), also available with logger.

The Process Scanner is compact size, priced very competitive. The unit can be drawn from the front for Easy servicing. Product Quality Certified.

Technical Data

Input	: Universal or RTD or Thermocouple or Voltage or Current
Display Range	: As per Input
No Of Channel	: 1 to 24 channels
Accuracy	: Better than ± 0.1 % FSD
Input Sampling	: 2 channels per second
Operating Voltage	: 24 VDC or 110 VAC or 230 VAC
Bezel Dimension	: 96X96X110 or 192X96X110 mm
Operating Conditions	: Temperature : 0 to 50 °C, Humidity : 0 to 80 % Rh

Ordering Guide

Model : TTS Series

Order Example

TTS-3113141

Code	1	2	3	4
Operating Voltage	24 VDC	110 VAC	230 VAC	Others
Input	Universal	RTD pt 100	Thermocouple	Current
No of Channel	8	12	16	24
Type	Scanner	Logger	Memory	Others
Communication	RS 232	RS 485	Printer port	Others
Thermocouple	IC- J	Cr/Al -K	Pt Pt Rh - S	Others
Cutout Size	92X92 mm	188X92 mm	-	Others



Since 1987

TEMPSEN DEVICES

Friendly Experts in Business

Old No:36/3, New No: 16, Alandur Road, Saidapet, Chennai-600 015
 Telefax : +91-44-23814758, 43302617, Mobile : +91-9445088368, Customer Care : +91-9841291758
 Email: tempsen@yahoo.com, solution@tempsendevices.net, web site: www.tempsendevices.net